

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

- 1-6. (Cancelled)
7. (Original) An apparatus comprising:
 - a driving circuit including an input and an output;
 - a first conductor including a first end and a second end;
 - a first input port for receiving a trigger signal coupled to the input of the driving circuit;
 - a second input port for receiving an event signal coupled to the first end of the first conductor;
 - an output port for outputting a hold signal coupled to the second end of the first conductor; and
 - a second conductor, having an impedance higher than an impedance of the first conductor, and coupled between the output of the driving circuit and a connection point on the first conductor.
8. (Original) The apparatus of claim 7 wherein the first conductor includes a low impedance microstrip.
9. (Original) The apparatus of claim 7 wherein the second conductor includes a high impedance microstrip having an impedance higher than an impedance of the first conductor.
10. (Original) The apparatus of claim 7, wherein the driving circuit comprises:

a third conductor, having a first end coupled to the first input port for matching the impedance of the trigger signal;

a matching circuit coupled to a second end of the third conductor for matching the level of the trigger signal to the driving circuit;

a sequential logic circuit, having an input coupled to an output of the matching circuit, for holding a signal corresponding to the state of the trigger signal; and

a buffer circuit having an enable input coupled to an output of the sequential logic circuit and having an output coupled to the output of the driving circuit.

11. (Original) The apparatus of claim 10 wherein the third conductor includes a low impedance microstrip.

12. (Original) The apparatus of claim 10 wherein the sequential logic circuit comprises a flip-flop.

13. (Original) The apparatus of claim 10 wherein the buffer circuit comprises a tri-state-buffer.

14. (Original) The apparatus of claim 10 wherein the matching circuit comprises a voltage divider.

15. (Original) The apparatus of claim 10 comprising a reset switch circuit coupled to a reset input of the sequential logic circuit for resetting the output of the sequential logic circuit.

16. (Cancelled)

17. (Currently amended) The system of claim 16 19 wherein each trigger signal is synchronized with an event signal such that the trigger signal occurs between a rising edge of the event signal and a falling edge of the event signal.

18. (Currently amended) The system of claim 16 19 wherein the initial state of each event signal is stored in the holding circuit after transition of the event signal to a subsequent state.

19. (Currently amended) ~~The system of claim 16~~ A system comprising:
a signal source for generating event signals and trigger signals;
a holding circuit for receiving the event signals and trigger signals, and for capturing the
event signals;
a device under test (DUT) for producing response signals in response to the event signals;
and
a measuring device for evaluating the DUT based on a comparison of the response
signals from the DUT with the captured event signals from the holding circuit,
wherein the holding circuit comprises:
a driving circuit including an input and an output;
a first conductor including a first end and a second end;
a first input port for receiving a trigger signal coupled to the input of the driving circuit;
a second input port for receiving an event signal coupled to the first end of the
first conductor;
an output port for outputting a hold signal coupled to the second end of the first
conductor; and
a second conductor, having an impedance higher than an impedance of the first
conductor, and coupled between the output of the driving circuit and a connection point on the
first conductor.

20. (Original) The system of claim 19 wherein the first conductor includes a low impedance microstrip.

21. (Original) The system of claim 19 wherein the second conductor includes a high impedance microstrip having an impedance greater than an impedance of the first conductor.

22. (Original) The system of claim 19, the driving circuit comprising:
a third conductor, having a first end coupled to the first input port for matching the impedance of the trigger signal;
a matching circuit coupled to a second end of the third conductor for matching the level of the trigger signal to the driving circuit;
a sequential logic circuit, having an input coupled to an output of the matching circuit, for holding a signal corresponding to the state of the trigger signal; and
a buffer circuit having an enable input coupled to an output of the sequential logic circuit and having an output coupled to the output of the driving circuit.

23. (Original) The system of claim 21 wherein the third conductor includes a low impedance microstrip.

24. (Original) The system of claim 21 wherein the sequential logic circuit comprises a flip-flop.

25. (Original) The system of claim 21 wherein the buffer circuit comprises a tri-state-buffer.

26. (Original) The system of claim 21 wherein the matching circuit comprises a voltage divider.

Applicant : Bradley A. Bloechel
Serial No. : 09/843,606
Filed : April 26, 2001
Page : 6 of 7

Attorney's Docket No.: 10559-400001 / P10337

27. (Original) The system of claim 21 comprising a reset switch circuit coupled to a reset input of the sequential logic circuit for resetting the output of the sequential logic circuit.